



# IF380/90R46

Ultra Sprayer • 160D • R-1



## TECHNICAL DATA

Design	<b>Ultra Sprayer</b>	Static Loaded Radius (mm)	<b>831</b>
Industry Classification	<b>R-1</b>	Rolling Circ (mm)	<b>5563</b>
Tyre Size	<b>IF380/90R46</b>	SRI	<b>925</b>
LI/SS	<b>160D</b>	Weight (kg)	<b>177</b>
FR/DW	<b>n/a</b>	Nominal Inflation Pressure (bar)	<b>3.0</b>
PR	<b>n/a</b>	Max Load (kg)	<b>4500</b>
TL/TT	<b>TL</b>	Tread Depth (mm)	<b>39</b>
Tyre Width (mm)	<b>361</b>	Recom'd Rim	<b>W13</b>
Overall Diameter (mm)	<b>1844</b>	Other approved rims	<b>n/a</b>

## LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (bar)										
	0.8bar	1.0bar	1.4bar	1.8bar	2.2bar	2.4bar	2.6bar	3.0bar	3.2bar	4.0bar	4.4bar
70	1930	2210	2800	3230	3415	3525	3755	4095	n/a	n/a	n/a
65	2120	2430	3075	3550	3750	3875	4125	4500†	n/a	n/a	n/a
10cycl	n/a	n/a	4760	5500	5820	6000	6400	7000	n/a	n/a	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor