



10-16.5

IT323 • 135A2 • SS



TECHNICAL DATA

Design	IT323	Static Loaded Radius (mm)	350
Industry Classification	SS	Rolling Circ (mm)	2312
Tyre Size	10-16.5	SRI	375
LI/SS	135A2	Weight (kg)	29
FR/DW	n/a	Nominal Inflation Pressure (bar)	5.2
PR	10	Max Load (kg)	2180
TL/TT	TL	Tread Depth (mm)	21
Tyre Width (mm)	249	Recom'd Rim	8.25
Overall Diameter (mm)	771	Other approved rims	n/a

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (bar)							
	1.4bar	1.7bar	2.4bar	2.8bar	3.1bar	3.8bar	4.1bar	4.5bar
10	815	940	1125	1220	1325	1475	1565	1605
5	945	1090	1305	1415	1535	1710	1815	1865
20	710	820	980	1065	1155	1285	1365	1400
25	690	795	955	1035	1125	1250	1325	1360
30	675	780	935	1015	1100	1225	1300	1335
40	650	750	900	975	1060	1180	1250	1285
10 cyclic	975	1125	1350	1465	1590	1770	1875	1930

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor