



IF320/105R54

Ultra Sprayer • 167D • R-1



TECHNICAL DATA

Design	Ultra Sprayer	Static Loaded Radius (mm)	949
Industry Classification	R-1	Rolling Circ (mm)	6238
Tyre Size	IF320/105R54	SRI	1025
LI/SS	167D	Weight (kg)	177
FR/DW	n/a	Nominal Inflation Pressure (bar)	4.4
PR	n/a	Max Load (kg)	5450
TL/TT	TL	Tread Depth (mm)	37
Tyre Width (mm)	328	Recom'd Rim	W10
Overall Diameter (mm)	2043	Other approved rims	W11

LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (bar)									
	1.4bar	1.8bar	2.2bar	2.8bar	3.0bar	3.4bar	3.6bar	4.0bar	4.4bar	4.8bar
70	2640	3050	3320	3755	3870	4210	4325	4550	4960	n/a
up to 65	2900	3350	3650	4125	4250	4625	4750	5000	5450†	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor