



# IF380/90R54

Ultra Sprayer • 171D • R-1



## TECHNICAL DATA

Design	<b>Ultra Sprayer</b>	Static Loaded Radius (mm)	<b>952</b>
Industry Classification	<b>R-1</b>	Rolling Circ (mm)	<b>6259</b>
Tyre Size	<b>IF380/90R54</b>	SRI	<b>1025</b>
LI/SS	<b>171D</b>	Weight (kg)	<b>203</b>
FR/DW	<b>n/a</b>	Nominal Inflation Pressure (bar)	<b>4.4</b>
PR	<b>n/a</b>	Max Load (kg)	<b>6150</b>
TL/TT	<b>TL</b>	Tread Depth (mm)	<b>39</b>
Tyre Width (mm)	<b>365</b>	Recom'd Rim	<b>W12</b>
Overall Diameter (mm)	<b>2051</b>	Other approved rims	<b>W13</b>

## LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (bar)									
	1.4bar	1.8bar	2.2bar	2.8bar	3.0bar	3.4bar	3.6bar	4.0bar	4.4bar	4.8bar
70	3050	3525	3755	4210	4435	4685	4825	5095	5595	n/a
up to 65	3350	3875	4125	4625	4875	5150	5300	5600	6150†	n/a

† Maximum load at recommended speed and inflation pressure.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor