



# 460/85R30

R14 • 145D • R-1



## TECHNICAL DATA

Design	R14	Static Loaded Radius (mm)	704
Industry Classification	R-1	Rolling Circ (mm)	4668
Tyre Size	460/85R30	SRI	725
LI/SS	145D	Weight (kg)	124
FR/DW	n/a	Nominal Inflation Pressure (bar)	1.6
PR	n/a	Max Load (kg)	2900
TL/TT	TL	Tread Depth (mm)	32
Tyre Width (mm)	485	Recom'd Rim	W14L
Overall Diameter (mm)	1538	Other approved rims	W15L, W16L, DW15L, DW16L

## LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (bar)									
	0.6bar	0.8bar	1.0bar	1.4bar	1.6bar	1.8bar	2.0bar	2.2bar	2.4bar	2.6bar
70	1455	1685	1930	2410	2640	2800	2900	3000	3075	3250
65	1600	1850	2120	2650	2900†	3075	3150	3250	3350	3550
50	1680	1945	2225	2785	3045	2320	3310	3415	3520	3730
40	1750	2025	2320	2900	3175	3365	3450	3560	3670	3885
30	1840	2130	2440	3045	3335	3535	3620	3735	3850	4080
25	1895	2190	2510	3140	3435	3645	3735	3850	3970	4205
15	2145	2480	2840	3550	3885	4120	4220	4355	4490	41755
10	2400	2775	3180	3975	4350	4615	4725	4875	5025	5325
10cycl	n/a	2240	2720	3605	4010	4505	4930	5080	5220	5370

† Maximum load at recommended speed and inflation pressure.