



# 14-17.5NHS

R14 • 121A8 • R-1



## TECHNICAL DATA

Design	R14	Static Loaded Radius (mm)	420
Industry Classification	R-1	Rolling Circ (mm)	2737
Tyre Size	14-17.5NHS	SRI	450
LI/SS	121A8	Weight (kg)	34
FR/DW	n/a	Nominal Inflation Pressure (bar)	2.1
PR	6	Max Load (kg)	1450
TL/TT	TL	Tread Depth (mm)	17
Tyre Width (mm)	334	Recom'd Rim	10.5
Overall Diameter (mm)	926	Other approved rims	10.5

## LOAD DATA

Max Speed (km/h)	Tyre load (kg) at various inflation pressures (bar)									
	1.1bar	1.4bar	1.5bar	1.8bar	2.1bar	2.2bar	2.4bar	2.8bar	3.0bar	3.1bar
50	910	1045	1105	1200	1320	1365	1455	1545	1640	1685
40	1000	1150	1215	1320	1450†	1500	1600	1700	1800	1850
30	1040	1195	1265	1375	1510	1560	1685	1770	1870	1925
15	1130	1300	1375	1490	1640	1695	1810	1920	2035	2090
10	1250	1440	1520	1650	1815	1875	2000	2125	2250	2315
10cycl <sup>^</sup>	1500	1725	1825	1980	2175	2250	2400	2550	2700	2775
5cycl <sup>‡</sup>	1670	1920	2030	2205	2420	2505	2470	2840	3005	3090

† Maximum load at recommended speed and inflation pressure.

<sup>^</sup> 600m max one-way.

<sup>‡</sup> 150m max one-way.

Want to know more? Get in touch with us at: Titan Distribution (UK) Limited, +44(0)845 2001972, or locate your nearest Goodyear Farm Tires distributor